



US009313626B2

(12) **United States Patent**
Shuster

(10) **Patent No.:** **US 9,313,626 B2**
(45) **Date of Patent:** **Apr. 12, 2016**

(54) **ALERT SIGNAL CONTROL USING MESSAGE PRIORITY**

(2013.01); *H04M 19/04* (2013.01); *H04W 4/027* (2013.01); *H04W 48/04* (2013.01); *H04W 64/006* (2013.01); *H04M 2250/12* (2013.01)

(71) Applicant: **Gary Stephen Shuster**, Fresno, CA (US)

(58) **Field of Classification Search**

CPC *H04W 48/04*; *H04W 4/12*
USPC 340/438; 455/418, 419, 344, 345, 455/456.4-456.6, 557

(72) Inventor: **Gary Stephen Shuster**, Fresno, CA (US)

See application file for complete search history.

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(56) **References Cited**

U.S. PATENT DOCUMENTS

(21) Appl. No.: **14/148,673**

6,360,187	B1 *	3/2002	Hermann	340/460
6,690,940	B1 *	2/2004	Brown et al.	455/456.4
6,782,240	B1 *	8/2004	Tabe	455/345
7,065,349	B2 *	6/2006	Nath et al.	455/418
7,181,229	B2 *	2/2007	Singh et al.	455/456.4
7,505,784	B2 *	3/2009	Barbera	455/345
7,844,666	B2 *	11/2010	Horvitz et al.	709/206
8,212,661	B2 *	7/2012	Shuster	455/345
8,446,270	B2 *	5/2013	Shuster	455/345
8,624,718	B2 *	1/2014	Shuster	455/345
2006/0121887	A1 *	6/2006	Chilukoor	455/412.2

(22) Filed: **Jan. 6, 2014**

* cited by examiner

(65) **Prior Publication Data**

US 2014/0120882 A1 May 1, 2014

Related U.S. Application Data

(63) Continuation of application No. 13/898,442, filed on May 20, 2013, now Pat. No. 8,624,718, which is a continuation of application No. 13/540,592, filed on Jul. 2, 2012, now Pat. No. 8,446,270, which is a continuation of application No. 12/470,857, filed on May 22, 2009, now Pat. No. 8,212,661.

Primary Examiner — John A Tweel, Jr.

(74) *Attorney, Agent, or Firm* — Coleman & Horowitz, LLP; Sherrie Flynn

(60) Provisional application No. 61/055,290, filed on May 22, 2008.

(57) **ABSTRACT**

(51) **Int. Cl.**


B60Q 1/00 (2006.01)
H04W 4/12 (2009.01)
H04W 48/04 (2009.01)
H04M 19/04 (2006.01)
H04W 64/00 (2009.01)
B60K 35/00 (2006.01)
H04W 4/02 (2009.01)

An electronic communication system provides text or voice messages to remote receiving devices, such as cell phones or PDAs. The receiving devices include a function for determining a message priority, prior to providing any audible alert signal indicating that the message is received. If an incoming message has a priority that is lower than a necessary threshold, the function prevents the audible alert signal from being generated at the time the message is received.

(52) **U.S. Cl.**

CPC *H04W 4/12* (2013.01); *B60K 35/00*

20 Claims, 2 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3

ALERT SIGNAL CONTROL USING MESSAGE PRIORITY

CROSS-REFERENCE TO RELATED APPLICATION

This application is a continuation of U.S. application Ser. No. 13/898,442, filed May 20, 2013, now U.S. Pat. No. 8,624,718, which is a continuation of U.S. application Ser. No. 13/540,592, filed Jul. 2, 2012, now U.S. Pat. No. 8,446,270, which is a continuation of U.S. application Ser. No. 12/470,857, filed May 22, 2009, now U.S. Pat. No. 8,212,661, which claims priority pursuant to 35 U.S.C. §119(e) to U.S. provisional application Ser. No. 61/055,290, filed May 22, 2008, which are hereby incorporated by reference, in their entireties.

BACKGROUND

1. Field

This application relates to mobile telephones and other mobile portable communications devices, and to controlling the alert signal for such devices.

2. Description of Related Art

Portable cellular telephones and handheld messaging devices generally include one or more transducers to provide audible, tactile or visible alert signals indicating various forms of incoming messages. Incoming messages may include, for example, live telephone calls, voice messages, electronic mail, and text messages. Users generally carry such portable phones and messaging devices on their person for much or all of the day, and consequently distracting alert signals may be emitted by the portable device at inappropriate times. Portable messaging systems often provide a means for disabling any desired alert signal, but these means require the user to manually disable the alert signal via a switch or user input command. Likewise, re-enabling the alert signal generally requires manual input. Users may find it inconvenient or difficult to consistently deactivate and reactivate the alert signal using a manual control means.

SUMMARY

The present technology provides for automatic control of an audible alert signal for a portable messaging device, based on priority information determined from the incoming message. The control may include controlling a quality of the alert signal based on the priority information, or disabling the alert signal entirely if the priority information falls below a threshold.

This technology also provides for automatic disabling and re-enabling of an alert signal for a portable messaging device, in response to sensory input collected by a sensor in communication with the messaging device. The sensor may be physically near the messaging device, connected to the messaging device via a suitable interface, incorporated into the same housing as the messaging device, or any combination of the foregoing. For example, a GPS sensor or other locating system may be integrated into a portable messaging device configured to respond to sensor input to determine, in conjunction with governmental, system operator, sender, or end user defined parameters, when the messaging device emits an alert signal as notification of incoming or received messages.

For example, when a cellular phone or other portable device receives sensor input indicating that it is in motion at a speed greater than a preset limit, or has recently been in such motion within a set time period, message delivery (or, alter-

natively, notice that a message has been delivered) may be delayed until such time that the device is not in motion (or has been not in motion for a set time period). In this manner, alert signal notification of inbound messages, phone calls, emails, SMS texts, or even pre-set alarms (such as an internally entered appointment reminder on the device) are delivered to the user in a manner that does not impair safety. Optionally, this setting may be changed by the user when the user is able to deal with such messages safely despite being in motion, such as when the user is a passenger in a vehicle, not the driver. In addition, the device may utilize location or motion information transmitted from the vehicle, may utilize data as to the cellular tower and distance from the tower (and increasing or decreasing signal strength indicating movement toward or away from a tower), or the fact that it is "paired" with a vehicle sound system (as via Bluetooth™) to indicate motion or potential motion.

A threshold may be defined requiring motion greater than a certain speed, with operating logic to ensure that motion under, for example, 5 miles per hour, is not sufficient to trigger disabling of the alert signal. Likewise, when motion drops below a predetermined threshold the alert signal may be re-enabled. So as an example, a user driving at 5 miles per hour has a portable messaging device (PMD) that works normally, but when he exceeds 5 miles per hour the PMD may sense this and switch to a mode where all alerts other than phone calls (or even including phone calls) are silenced until the vehicle reaches a speed under 5 miles per hour again.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention, in accordance with one or more various embodiments, is described in detail with reference to the following figures. The drawings depict embodiments of the invention, by way of example.

FIG. 1 shows an example of a portable messaging device with alert signal control means.

FIG. 2 shows an example of a system using an automobile and wireless transmitter for alert signal control.

FIG. 3 shows a method 300 for controlling alert signaling in a portable messaging device.

DETAILED DESCRIPTION

FIG. 1 shows an exemplary portable messaging device 100 including familiar interface components such as a display screen 102, keypad 104, microphone 106, audio transducer 108 and housing 110 sized for handheld use. A circuit 112 (shown schematically) may be enclosed in the housing 110.

Circuit 112 may comprise various components in electronic communication with one another, including a cellular transmitter/receiver 114 connected to a central processor 116. CPU 116 may be connected to receive input from the keypad, microphone, or other input device, and operates system and application software stored in system memory 118. CPU 116, either directly or via an interface circuit (not shown) may drive an audio output transducer 120 for outputting an alert signal and/or audio message content. Other output signaling devices may also be used, such as a mechanical vibrator for outputting a tactile alert signal or a signal light, such as one or more L.E.D.'s, for providing a visual alert. The display 102 may also be used to provide a visual alert signal. The CPU, memory, and cellular transmitter/receiver may be considered core components for performing primary communication functions of device 100.

Circuit 112 may further comprise ancillary components for performing sensing functions, or for communicating with an

external sensor. By way of example, two such components are shown, a wireless frequency-hopping spread spectrum (e.g., Bluetooth™) module **122** for communicating with external Bluetooth-enabled devices, and a Global Positioning System (GPS) receiver for determining geographical location. Either or both of these components may be used. In this disclosure, embodiments using GPS or Bluetooth™ modules are discussed in more detail, but the technology is not limited thereby. Other useful sensors may include a light sensor, enabling automatic control of the alert signal responsive to external impinging light levels or temporal patterns, or a microphone for enabling similar control in response to external sound levels and patterns. Circuit **112** may also include a system clock or timer for measuring a current time, or elapsed time.

Alert signal control as described herein should be distinguished from command-based control. The Bluetooth™ unit **122**, the GPS receiver **124**, and other input sensors (if used) are not used merely for command control of the auto-disable feature. Instead, sensors are used for determining a present environmental status of the mobile device, and then decision logic is applied using the CPU in response to sensor input, to determine how alert signals for incoming messages should be controlled. Therefore, the portable device **100** responds differently to incoming messages depending on an external measured environmental state that is determined without command input. Of course, the use of environmental-based alert signal control need not exclude command-based control, of which complementary use may often be desirable. For example, circuit **112** may be configured to permit configuration of an auto-alert disable system in response to user command input.

One environmental variable of interest in alert signal control may include velocity. It may be desirable to mute (disable) the alert signal when the phone is moving at greater than a specified speed. A current velocity may be easily determined by reference to a GPS receiver and a system clock or timer. Other methods of determining location may also be suitable, such as by triangulation from any other known transmitters that make up a cellular network. However with present technology GPS locating is both accurate and relatively inexpensive, and may provide a suitable means for determining the mobile device's present location.

In lieu of an internal GPS receiver **124**, device **100** may obtain its location and/or speed from any external source. This may be conveniently accomplished via a Bluetooth™ transmitter/receiver as currently implemented in many cellular phones. Circuit **112** may periodically scan for an authorized external Bluetooth™ signal to obtain environmental data. For example, a Bluetooth™ transmitter/receiver **202** may be integrated into the electrical system of an automobile **200**, as shown in FIG. 2. As such, the device **100** may have access to GPS location data via a GPS receiver installed or located in the automobile. Device **100** may also receive current velocity information from the speedometer of car **200** via the Bluetooth™ interface **202**. Use of Bluetooth™ is merely exemplary, and alternative communication standards may also be used, including but not limited to wired or wireless standards such as USB, wireless USB, Zigbee™ and UWB.

Device **100** may also determine its relative location inside car **200** via the Bluetooth™ component **202** or other transmitter. For example, relative signal strength or triangulation may be used within the car interior, if so equipped. In the alternative, the car **200** or device **100** may be configured to ask the user where in the car the phone is located, in response to detecting that it has entered into the vehicle. For example, when a user carrying device **100** enters car **200**, the presence

of the phone may be detected and an onboard computer may output a verbal question such as "Is John a driver or passenger?" to which the user may reply "passenger" or "driver" as the case may be. The onboard computer may inform device **100** of the response to the query. The mobile device **100** may control the alert signal in accordance with the received response, for example, by disabling the alert signal on a speed-sensitive basis only if the response or other sensor data indicates that the mobile device is being used by the driver. The driver will therefore not be distracted by alert signals from device **100** while driving the car above a defined threshold speed, which may be any number of zero or greater.

Device **100** may also consider message parameters when determining whether to disable alert signaling. For example, certain message senders may have a capability to mark some messages or incoming calls as "urgent." Device **100** may be configured to selectively disable alert signals for incoming messages that are not marked as "urgent" by an authorized sender, while providing alert signals for urgent messages regardless of sensor input, or only in a narrower range of environmental conditions. For example, device **100** may provide alert signals for "urgent" marked messages while moving up to speeds of 60 miles per hour and for all other messages while moving up to five miles per hour.

Use of a self-contained locating and velocity-measuring system in device **100** may be advantageous for other reasons. For example, a portable communication device equipped with a GPS locating system may provide various location-based services, including navigational guidance and location-specific advertising. Use of the GPS system for velocity determination in such a GPS-equipped device may be merely incidental, and therefore may add negligible cost to the device.

FIG. 3 shows a method **300** for controlling alert signaling in a portable messaging device, such as may be performed using software or firmware operating in a device as described herein. Method **300** represents a performance loop that may be initialized shortly after powering up the device. A computer-readable medium may be used to store program instructions, that when executed by a processor of the portable messaging device, cause the device to perform as described herein below. After the loop is initialized, the device may scan for input **302** to one or more ports capable of receiving sensor (e.g., GPS) input. Scanning may be done periodically, and/or in response to an interrupt originating from a sensor device. In the alternative, or in addition, the device may periodically request sensor input from a connected sensor, which may respond to the device's requests with sensor data. The device may also wirelessly broadcast a query signal seeking a response from any sensors that may be available in the immediate area.

After scanning for incoming sensor data, the device may receive and process sensor data **304**. The sensor data may be time stamped and held in a memory of the device for later use. In the case of velocity determination, two or more of the most recent positional sensor data (indicating a current position of the sensor) may be held in system memory. In the alternative, or in addition, the device may calculate a current velocity and store in memory. Sensor data may be processed as necessary to provide useful input for alert signal controlling. For example, a feature may be provided wherein the volume or intensity of the alert signal is modulated in response to ambient noise. The noisier the ambient environment, the louder the alert signal provided, and conversely the alert signal volume may be diminished in quieter environments. To accomplish this control, the processor may use microphone input to calculate an average noise level over a recent time slice, for

5

example, for the most recent second or more recent ten seconds. The calculated noise level may then be stored in system memory for use in alert signal control. Similar use of sensor data may be used to silence or lower the volume of the alert signal when the environmental light levels are low.

The portable messaging device may normally be in a wait state **306**, waiting to receive an incoming message. During waiting, the device may periodically cycle through scanning, receiving and storing sensor data as described above. The wait state may be interrupted when an incoming message is received **308**. The feature of automatic signal disabling or automatic volume control as described herein may be subject to manual control, so that a user of the device may shut off this feature when it is not desired. Thus, before executing an alert signal control routine, the device may determine whether or not the automatic alert signal control feature has been temporarily turned off at **310**. If automatic control has been disabled, the device may output an alert signal **312** according to default or user-specified parameters, and dispose of the incoming message (whether phone call, text message, electronic mail, or other) in a normal fashion **314**.

If automatic control has been enabled **310**, the device may determine a most recent or a present environmental state **316** of the device by retrieving most recent stored sensor input from system memory. In the alternative, sensor input may be solicited and received in response to receipt of the incoming message **308**. Examples of environmental state may include, for example, the position and velocity of the device, acceleration of the device, ambient noise level, ambient light level, or any other sensor-based measure that may be useful for controlling an alert signal. Optionally, the device may determine a message status **318** with respect to alert signal control. Message metadata or other characteristics may indicate a special status used to modulate the alert signal, for example "message type," (e.g., "voice call," "e-mail" etc.) "urgent," "normal," or "low-priority." Status indicators such as these may be used to determine how to control that alert signal in conjunction with the environmental indicators.

After collecting environmental and (optionally) message parameters, the portable messaging device may evaluate the parameters against defined rules to determine whether or not conditions have been satisfied **320** for providing an immediate alert signal. Various exemplary rules have been described above. For example, the alert signal may be disabled if the device is moving at greater than a threshold velocity, if the ambient light levels are too low, etc. Even an ambient temperature may be used as input to a control scheme, as it may indicate whether or not the device is being worn close to a user's body. If conditions for providing an alert signal are not satisfied, the device does not output an alert signal **322** at that time. The device may delay output of the alert signal and may hold the incoming message in a memory **324**, and wait **306** until environmental conditions change to satisfy conditions for providing an alert. Live messages such as incoming voice calls may be rolled over to voice mail while other messages may be placed in a message inbox. During a wait period, additional sensor input may be scanned for **302** or received **304**. Program execution may then loop periodically back to environmental testing **316** and **320**, so that the alert signal can be re-enabled once environmental conditions (e.g., device velocity decreased to safe level) are satisfied **320**.

If conditions for providing an alert signal are satisfied **320**, the device may determine how to modulate the alert signal **326** in response to environmental or message parameters. Different signals may be provided based on message priority type or urgency level. The volume or intensity of the alert signal may be controlled based on sensor input as previously

6

described, for example, by changing the alert signal volume or changing the alert tone. In the alternative, the alert signal is not modulated and step **326** is omitted. The device may then output the alert signal **312**, and dispose of the message **314** in a conventional fashion.

The method **300** merely exemplifies a control scheme for controlling an alert signal in response to environmental sensor input. The present technology is not limited by this example.

The invention claimed is:

1. A portable messaging device, comprising:
 - a wireless receiver;
 - a processor coupled to the wireless receiver;
 - an audio transducer coupled to the processor, for providing audible alert signaling in response to incoming messages;
 - a memory coupled to the processor; the memory holding program instructions that when operated by the processor, cause the portable messaging device to obtain message priority information from incoming messages, and control an audible feature of the audible alert signaling based at least in part on the priority information.
2. The portable messaging device of claim 1, wherein the program instructions are further configured to selectively disable the audible alert signaling in response to determining, for each one of the incoming messages, that a message priority specified by the message priority information is not higher than a defined priority threshold.
3. The portable messaging device of claim 2, wherein the program instructions are further configured for holding the incoming message for which the alert signaling is automatically disabled in the memory until a later time.
4. The portable messaging device of claim 1, further comprising a velocity sensor communicatively coupled to the processor, wherein the program instructions are further configured for automatically disabling the audible alert signaling for an incoming message for which the audible alert signaling is not disabled based on the priority information, in response to determining, based on information from the velocity sensor, that a current velocity of the portable messaging device exceeds a threshold.
5. The portable messaging device of claim 4, wherein the program instructions are further configured for automatically re-enabling audible alert signaling for incoming messages, in response to determining that the current velocity of the portable messaging device no longer exceeds the threshold, based on information from the velocity sensor.
6. The portable messaging device of claim 4, further comprising a wireless receiver coupled to the processor and configured to receive the information from the velocity sensor from an on-board transmitter in a vehicle.
7. The portable messaging device of claim 4, wherein the velocity sensor comprises a GPS receiver configured to receive a GPS locating signal and a timer.
8. The portable messaging device of claim 7, wherein the program instructions are further configured for determining the current velocity using the GPS locating signal and a time signal from the timer.
9. The portable messaging device of claim 4, wherein the program instructions are further configured to measure a duration for which a current velocity is maintained continuously above the threshold, and automatically disabling audible alert signaling for incoming messages is further conditioned on determining that the duration exceeds a minimum time period.

10. A method comprising:
receiving an incoming wireless message, by the messaging
device;
reading a priority level assigned to the incoming message;
and

controlling emission of an audible alert signal from the
portable messaging device in response to the priority
level, wherein an audible feature of the audible alert
signal is based on at least in part on the priority level.

11. The method of claim 10, wherein the controlling com-
prises preventing the portable wireless messaging device
from emitting any audible alert signal in response to deter-
mining that the priority level is lower than a defined level.

12. The method of claim 11, further comprising holding the
incoming message in a memory of the portable wireless mes-
saging device until a later time, if the device is prevented from
emitting the audible alert signal.

13. The method of claim 10, further comprising determin-
ing a current velocity of the portable wireless messaging
device using a processor of the portable messaging device
coupled to a velocity sensor, based on information from the
velocity sensor;

determining that the current velocity of the portable mes-
saging device is greater than a threshold;
preventing emission of the audible alert signal from the
portable messaging device in response to the determin-
ing.

14. The method of claim 13, further comprising determin-
ing the current velocity by receiving a velocity signal from a
velocity sensor installed in a motor vehicle.

15. The method of claim 13, further comprising re-en-
abling the audible alert signal for signaling an incoming mes-
sage, in response to determining that the current velocity is
not greater than the defined threshold.

16. A non-transitory computer-readable medium encoded
with instructions that, when executed by a processor, cause a
portable wireless device to:

receive an incoming wireless message, by the messaging
device;

read a priority level assigned to the incoming message; and
control emission of an audible alert signal from the por-
table messaging device in response to the priority level,
wherein an audible feature of the audible alert signal is
based on at least in part on the priority level.

17. The computer-readable medium of claim 16, further
encoded with instructions that, when executed by the proces-
sor, cause the portable wireless device to control the emission
at least in part by preventing the portable wireless messaging
device from emitting any audible alert signal in response to
determining that the priority level is lower than a defined
level.

18. The computer-readable medium of claim 16, further
encoded with instructions that, when executed by the proces-
sor, cause the portable wireless device to hold the incoming
message in a memory of the portable wireless messaging
device until a later time, if the device is prevented from
emitting the audible alert signal.

19. The computer-readable medium of claim 16, further
encoded with instructions that, when executed by the proces-
sor, cause the portable wireless device to:

determine a current velocity of the portable wireless mes-
saging device using a processor of the portable messag-
ing device coupled to a velocity sensor, based on infor-
mation from the velocity sensor;

determine that the current velocity of the portable messag-
ing device is greater than a threshold;

prevent emission of the audible alert signal from the por-
table messaging device in response to the determining.

20. The computer-readable medium of claim 19, further
encoded with instructions that, when executed by the proces-
sor, cause the portable wireless device to re-enable the
audible alert signal for signaling an incoming message, in
response to determining that the current velocity is not greater
than the defined threshold.

* * * * *