



US007804744B2

(12) **United States Patent**
Shuster

(10) **Patent No.:** **US 7,804,744 B2**
(45) **Date of Patent:** **Sep. 28, 2010**

(54) **OPTICALLY-READABLE DISK WITH COPY PROTECTION DEVICE**

(76) Inventor: **Gary Stephen Shuster**, 8630 N. 4th St.,
Fresno, CA (US) 93720

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 281 days.

(21) Appl. No.: **12/167,655**

(22) Filed: **Jul. 3, 2008**

(65) **Prior Publication Data**

US 2009/0073817 A1 Mar. 19, 2009

Related U.S. Application Data

(63) Continuation-in-part of application No. 11/744,123,
filed on May 3, 2007.

(51) **Int. Cl.**
G11B 11/00 (2006.01)
G11B 7/24 (2006.01)

(52) **U.S. Cl.** **369/13.35**; 369/275.3; 369/288

(58) **Field of Classification Search** 369/275.3,
369/13.38, 13.35, 13.39, 30.09, 30.04, 288,
369/283, 53.21

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,338,625 A * 8/1994 Bates et al. 429/322
5,558,957 A * 9/1996 Datta et al. 429/127

5,787,068 A 7/1998 Arps et al.
5,832,088 A 11/1998 Nakajima et al.
6,266,299 B1 7/2001 Oshima et al.
6,597,648 B1 7/2003 Yeo et al.
7,142,075 B1 * 11/2006 Roesler et al. 335/78
2003/0149885 A1 8/2003 Fang et al.
2003/0179663 A1 9/2003 Tomita
2003/0185128 A1 10/2003 Shoji et al.
2004/0022542 A1 2/2004 Atkinson
2005/0169145 A1 8/2005 Yumiba et al.
2007/0097837 A1 * 5/2007 Marshall et al. 369/116

FOREIGN PATENT DOCUMENTS

JP 8-55342 2/1996

* cited by examiner


Primary Examiner—Ali Neyzari

(74) *Attorney, Agent, or Firm*—Connolly Bove Lodge & Hutz
LLP; Jonathan A. Jaech

(57) **ABSTRACT**

An optically-readable disk includes a device that disrupts readability of the disk when the disk is spun at an angular velocity substantially greater than required to play the disk in its intended playing device, or when a defined integral of velocity and time is exceeded. The device may include a fluid container that disperses a data-disruptive fluid. The device may include a membrane or layer that is disrupted when the disk is rotated above a defined angular velocity, or when a defined integral of velocity and time is exceeded. The device may include an electro-optical material that is activated by an electrical signal from a controller in response to an input from a sensor responsive to motion of the disk.

20 Claims, 4 Drawing Sheets






FIG. 1A




FIG. 1B




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10

1

OPTICALLY-READABLE DISK WITH COPY PROTECTION DEVICE**RELATED APPLICATION**

The present application is a continuation-in-part of application Ser. No. 11/744,123, filed May 3, 2007, the entirety of which is incorporated herein by reference.

BACKGROUND**1. Field of the Invention**

The present invention relates to an optically readable disk designed to inhibit access of encoded content under defined mechanical conditions, such as, for example, by being rendered unreadable when the disk is spun at speeds higher than the disk's standard playback speed.

2. Background

Optically-read disks present a common and popular way of storing data and other content. Specifically, consumer entertainment content in the form of movies, music and other media are commonly recorded on disks and sold to consumers. Optically-read disks include, for example, audio CDs, CD-ROMs, DVDs, HD-DVDs, and Blu-Ray disks.

Unfortunately, the content recorded on optically-read disks can be illegally reproduced in violation of copyright laws. Such unauthorized reproduction is especially widespread due to the increasing availability and affordability of equipment used to reproduce the content recorded on an optically-read disk.

There have been various attempts to inhibit such copying, the majority of which focus on various encryption methods designed to prevent copying. In addition, some optical disks may be protected by means of noncontiguous data files separated by barriers designed to interrupt a disk player's reading of the disk.

Previous security devices and techniques aimed at preventing the illegal copying of protected content recorded on optically-readable disks, besides being expensive to implement, have focused on methods to overcome, and stay one step ahead of, disk player and disk recording technology. Unfortunately, as the security features implemented to prevent illegal copying becomes more sophisticated, they are quickly rendered obsolete due to the continuing and rapid advancement of disk recording technology. Accordingly, there is a need for an optical disk having a copy protection feature which overcomes the aforementioned deficiencies of the prior art.

SUMMARY

The present invention is directed to an optically-readable disk having protection against unauthorized reproduction of the data recorded on the disk.

When a user inserts a disk into a disk player for viewing of the data, the disk player spins the disk at a speed sufficient to enable the disk player to read the data so the user can view the content recorded on the disk. A typical commercially-available disk player intended solely for the purpose of viewing disk content, for example, a DVD player that is connected to a television, reads the disk at the slowest speed possible for playback and viewing.

Other disk players that are widely available, for example, those available as a component of a home computer system, routinely spin the disk at speeds much higher than what is required for the disk player to simply read the disk content for playback. These high speed disk players allow users, in con-

2

junction with disk recording hardware, to copy the disk content in a much shorter time period than what would be required if the user were to attempt to copy the disk while the disk was spinning at the slower playback speed.

Accordingly, if a user wished to make a copy of a disk, the user would naturally use a readily available and inexpensive disk reader that would spin the disk at a higher rate of speed than the slower playback speed. This allows the user to copy the disk content in a much shorter time period. It also provides a user easy means to pirate copyrighted material by making multiple copies of the disk for illegal distribution. For example, it would take a copier two hours to copy a two hour movie recorded on a DVD where the disk was spinning at normal playback speed. However, a user could copy the same two hours worth of content in less than 10 minutes if the disk reader spun the disk at higher speeds.

The present technology is designed to frustrate a user's ability to copy the content of the disk by only allowing the disk to be read at the slower playback speed. If the disk is read at the faster "copying" speed, the disk is rendered unreadable and copying is thwarted.

In an embodiment, an optically-readable disk contains a small capsule or container attached to or embedded in its reading surface. The capsule or container is designed and attached to the disk so as not to interfere with a disk reader's reading of the disk and so as not to interfere with the stable spinning of the disk while being played. The capsule contains an obscuring compound such as ink or other opaque or reflective fluid. The capsule's membrane is constructed of a material that remains stable at low "read-only" or "playback" speeds. However, if the disk is inserted into a disk player and the disk is spun at speeds higher than the minimum speed necessary to read the disk and playback the disk content, the material of the capsule will disintegrate or otherwise destabilize. As a result, the capsule will fail and release its contents onto the reading surface of the disk, obscuring the reading surface and rendering the disk unreadable by the disk reader.

In another embodiment, a deformable membrane is attached to the reading surface of the disk in such a manner to permit reading of the disk at slow, playback speeds. When the disk is spun at speeds higher than the playback speeds, the membrane deforms. This prevents the disk content from being read by the disk reader.

In another embodiment, a deformable membrane is attached to either surface of the disk so as to permit reading of the disk at slow, playback speeds. However, when the disk is spun at speeds higher than the playback speeds, the membrane expands either above the surface of the disk or beyond the edges of the disk so as to physically interfere with the disk player's components, thus rendering the disk unplayable by the disk player.

In another embodiment, a thin membrane is adhered to the reading surface of the disk using an adhesive such that, when the disk spins in the disk reader at slow, playback-only speeds, the membrane remains uniformly adhered to the reading surface of the disk and does not interfere with reading data on the disk. However, if the disk player spins the disk at speeds higher than slow, playback-only speeds, the resulting forces may cause the adhesive to fail or introduce discontinuities in the membrane surface which causes the membrane to reflect or obscure the reading surface of the disk in a manner which renders the disk unreadable.

In other embodiments, an electro-optical material layer may be interposed between at least a portion of a data layer of the disk and the disk reading surface. An electro-optical material is a material having a least one optical property that changes in response to an electrical signal; for example, trans-

3

parency, color, or reflectivity may change when a voltage or current is applied across the material. Examples of electro-optic materials that may be used in a disk layer may include, without limitation, liquid crystal materials and electrochromic films and gels. The electro-optical layer may be configured such that, when activated by an electrical signal, the electro-optical layer renders the optical data layer unreadable by an optical disk reader. The electro-optical layer may be restored to a deactivated state thereby restoring readability to the data layer by applying a second electrical signal, stopping the electrical signal, passively by passage of time, or some combination of the foregoing. The disk may further include a suitable sensor, such as an accelerometer, operatively associated with a controller disposed to apply an electrical signal to the electro-optical layer. When the controller receives a signal from the sensor indicating that the disk is rotating at a speed in excess of a maximum permitted angular velocity, or is accelerating in excess of a maximum permitted acceleration, the controller causes an electrical signal to be applied to the electro-optical layer, thereby rendering the disk temporarily or permanently unreadable.

A more complete understanding of the method and system for preventing the copying of an optically-readable disk will be afforded to those skilled in the art, as well as a realization of additional advantages and objects thereof, by a consideration of the following detailed description of various embodiments. Reference will be made to the appended sheets of drawings which will first be described briefly.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1A is a breakaway plan view showing a planar structure of an optically-readable disk **100**, according to a first embodiment showing the fluid containing container **101**, attached to the disk surrounding the drive rotation hole, **102**, of the disk.

FIG. 1B is a planar view of the fluid containing container configured in a toroid shape to accommodate attachment of the container on the disk according to the first embodiment.

FIG. 2 is a breakaway plan view showing an alternative embodiment having a fluid-containing container located near the rim of an optically-readable disk.

FIG. 3 is a sectional structure view of the optically-readable disk showing the plurality of layers of the disk, including a deformation layer according to an embodiment.

FIG. 4 is a sectional structure of an optically-readable disk according to a embodiment showing a membrane layer adhered to the disc.

FIG. 5 is an enlarged view of a container showing the suspension of microspheres within the fluid contained in the container, configured to penetrate the container membrane when the container is subjected to sufficient centrifugal force.

FIG. 6 shows an exemplary fluid container including a structure for fluidic integration of centrifugal force over time.

FIG. 7 is a block diagram showing a configuration for a circuit activated penetrating member attached to the container membrane and configured to pierce the container membrane upon the detection of sufficient, sustained centrifugal forces.

FIG. 8 is a schematic diagram showing a cross-section of an exemplary optical disk with an electro-optical layer.

FIG. 9 is a schematic diagram showing a partial plan view of an exemplary disk with an electro-optical layer.

4

FIG. 10 is a schematic diagram showing a cross-section of an exemplary disk with an electro-optical layer.

DETAILED DESCRIPTION

The present technology provides features that are particularly applicable to the prevention of the copying of optical disks, for example, CD, CD-ROM, DVD, DVD-ROM, HD-DVD, or Blu-Ray™ disks. Specifically, optical disks are primarily purchased (or rented) by users for playback of content encoded on the disk to produce audio-visual output on a user's television using a DVD, HD-DVD or Blu-Ray™ player, to produce music output on the user's music player, to play a game using the user's game player, and so forth. When used for this purpose, the receiving end-user player will spin the optical disk only at the slow, playback speed. If a user wishes to make an illegal copy of optical disk content, the user would insert the optical disk into a disk player that would spin the disk at speeds much faster than playback speeds used for simple viewing of the encoded disk content. In the detailed description that follows, like element numerals are used to indicate like elements appearing in one or more of the figures.

FIG. 1A illustrates certain features according to an exemplary first embodiment. Specifically, it shows a planar structure of an optically-readable disk **100** with a toroid shaped container **101**, attached to the center of the disk surrounding the drive rotation hole **102** of the disk. This embodiment permits a disk player to spin the disk without any interference from the container. This embodiment also permits the disk player to read the data reading area **104**, without interference from the container. The data reading area **104** may include encoded digital data designed to be read by an optical pick-up device and decoded by a player to produce audio-visual, audio, or visual output for human consumption or to provide software for operation by a computer.

As used herein, a "readable" disk or area is one that may have its microscopic encoded digital data read by an optical pick-up device for use in an electronic player or computer. It should be apparent that optical disks may also include printed surfaces and labels designed to be read by the human eye; as used herein, a readable surface does not include these types of printed surfaces and labels.

When the container is subjected to angular velocities substantially greater than an angular velocity corresponding to a playback speed of the optical disk, the container may rupture, leak, or allow its contents to diffuse into an interior of the disk. The placement of the container **100** in this embodiment may allow for the container to be subject to such angular velocities upon the spinning of the disk substantially faster—for example, at least 50% or 100% faster—than needed for playing the disk in a CD player, DVD player, or the like. Also, in this embodiment, the placement of the container provides an effective means for the release and disbursement of the fluid **112** (as shown in FIG. 2) onto the data reading area upon the container membrane's **110** collapse (as shown in FIG. 1B). This disbursement of the fluid onto the data reading area thus interferes with the disk player's reading of the data recorded on the disk and therefore prevents copying of the data recorded on the disc.

Optionally, released fluid may be distributed into an interior of the disk via one or more transparent channels **105**. Released fluid may comprise a gas or liquid. The released fluid may itself be opaque or reflective, or may cause a latent material distributed over a surface of the disk to become opaque or reflective. In the alternative, or in addition, the fluid may comprise a reactive material that reacts with materials in the disk's optically-readable layer to destroy or degrade read-

5

ability of the disk, or the structural integrity of the disk. Preferably, the released liquid remains contained inside the disk after it is released from its container, or is of a nature so as to not harm adjacent people, devices, clothing, or the like, if released from the disk. Fluid-containing structures in an interior of a disk may be structured so that fluid of a certain viscosity will not flow into an area where data will be rendered unreadable unless the disk is spun for a prolonged period of time that is much longer than normal playing time, is spun at velocities exceeding normal playback velocity, or come combination of the foregoing. In addition, fluid-containing structures may be configured so that fluid will out of data areas to an origination region if the disk is handled in a certain fashion. For example, fluid may flow out of data areas if the disk is stored on edge for a prolonged period of time. Such a configuration may permit functioning of a disk to be restored after data is temporarily obscured.

FIG. 2 shows an alternative embodiment comprising a fluid **152** contained in a container **153** near an outer rim **157** of an optically-readable disk **150**. Container **153** may be disposed adjacent a puncturing structure **155**, which may comprise, for example, one or more small teeth or needles configured to puncture the container walls. When disk **150** is spun at normal playing speed, the centrifugal force acts on the container **153** in the direct indicated by arrow **156**. However, the container and surrounding structures are configured such that the centrifugal force does not puncture or otherwise unseal the container. At substantially higher speeds, however, the container may be pressed against cutting teeth **155** or similar structure, releasing the fluid **152** into an interior of the disk, e.g., via a channel or partially open layer.

FIG. 3 shows a sectional structure of the disk in an alternative embodiment. Specifically, an optically-readable disc **100** may be generally constructed of a plurality of layers, including a top layer **200**, which comprises the top of the disk, an optically-readable layer **201** upon which the data is recorded, as well as a reflective layer **202** and a transparent layer **204** both of which facilitate a disk player's reading of the data recorded on the optically-readable layer of the disk.

A deformation layer **203** may be interposed between the reflective layer and transparent layer. This deformation layer may be constructed of a material that is stables and permits a disk reader to read the data recorded on the optically-readable layer **201** when the disk is repeatedly spun at an angular velocity no greater than for normal playback in a consumer viewing device. When the disk is spun at an angular velocity substantially greater than the angular velocity required to read the data for playback in an end-user device, the deformation layer **203** may cavitate, crack, craze, deform, or otherwise alter its light-transmitting or reflecting properties, thereby disrupting or interfering with the disk reader's ability to read the data recorded on the disk. Based on this second preferred environment, the deformation layer can accomplish this disruption or interference by partially or entirely obscuring the optically-readable layer, which optically-readable layer is positioned behind the deformation layer. In addition, disruption of the reading of the disk can be accomplished by having the deformation layer deform or stretch beyond the edges of the disk thus causing physical interference with the disk reader.

Another embodiment has the deformation layer secured to either the bottom of the transparent layer **204** or top layer **200**. In this embodiment, the deformation layer is configured so that when it deforms, it can expand beyond the physical boundaries of the disk. Again, the purpose of such deformation is to physically interfere with the disk reader and thus prevent the reading of the disk.

6

In an embodiment, the deformation layer may comprise an elastic material or a visco-elastic material with a shape memory. After deforming during excessively high-speed rotation, the layer may return to its original configuration after the disk stops spinning, such as by laying the disk on a flat surface. Restoration of the original shape may occur relatively quickly, for example, in less than one minute or less than one hour, or relatively slowly, for example, longer than one hour or longer than one day. In addition, or in the alternative, it may be possible to restore the deformation layer by exposure to a certain environment, for example, to an elevated temperature, infrared or ultraviolet radiation, or by exposure to a specific liquid or gas. This may permit the functioning of disks to be restored after a copy-protection feature is activated.

FIG. 4 shows another alternative embodiment wherein a membrane layer **205** may be adhered to the transparent layer **204**. The membrane layer may include an adhesive that is configured to bond the membrane layer to the transparent layer at slow, disk reading speeds. When the disk is spun at angular velocities substantially greater than the disk reading speed, the adhesive fails causing the membrane layer to separate from the transparent layer. Such separation may obscure the optically-readable layer **201** or will otherwise interfere with the disc reader's ability to read the data recorded on the optically-readable layer.

Whether a container with fluid or a deformation layer is used, the selectively-obscuring element should be more sensitive to centrifugal forces and less so to forces acting in other directions, for example, such as may arise from flexing the disk during handling or accidentally dropping the disk. A material, container, or device may be used that is not activated by impulses or forces acting for a relatively shorter periods of time. For example, in an embodiment, the disk may include an electronic, micro-mechanical, or fluidic device that integrates excess centrifugal force over time. Centrifugal force below a defined threshold and non-centrifugal forces may be ignored by the device, but centrifugal forces above a defined threshold are integrated over time until a triggering threshold is reached. For example, a micro-fluidic device may be configured such that centrifugal force above a defined threshold causes a fluid to flow through an orifice into a container. Surface tension of the fluid prevents flow when centrifugal force is below the threshold level. When the container is full, the device triggers activation of the obscuring device. Electrical or mechanical analogs of fluidic force-integrating devices may also be used.

The use of a force-integrating activation device may also be used to configure a disk so that it is rendered unreadable if spun even at relatively low velocities, i.e., normal playback speeds, for more than a defined period of time. For example, a disk could be designed to remain readable for a single play, or for any number of plays, after which it is rendered unreadable. However, because a force-time integral is used as the triggering factor, the disk may remain readable for any desired length of time under the control of the disk consumer, if it is not spun at all or is not spun for longer than the defined time.

FIG. 5 shows any exemplary structure of a container and contained fluid such as may be used in the embodiments exemplified by FIGS. 1A and 2, and that may be configured to integrate centrifugal force. Specifically, the container **100** may contain a fluid **102**, such as an ink or solvent, configured for obscuring or otherwise rendering unreadable the reading surface of the disk upon its release from the container. Micro-spheres **103** may be suspended in the contained fluid, configured to degrade the membrane **101** of the container when they

come in contact with the membrane. Under sufficient and sustained centrifugal force, sufficient numbers of microspheres should come into contact with the membrane, causing the membrane to rupture, leak or otherwise release the fluid onto the disk. Container **100** may be configured with one or more depressions or pockets **117** in the radial direction that gradually collect microspheres when the container is subjected to centrifugal force above a defined threshold. Below the threshold, the viscosity of fluid **102** may prevent migration of microspheres to the membrane walls. After a sufficient number of microspheres have collected near a membrane wall, the membrane may rupture, releasing fluid **102**.

FIG. **6** shows a portion of an exemplary container **101** incorporating a fluidic structure configured to integrate centrifugal force over time. Container **101** may be located near or in the hub of an optically-readable disk **100**, and may be generally toroid in shape. The fluidic structure may comprise one or more nozzles **120** or openings in the membrane wall **110**. Fluid **112** and openings **120** may be configured such that, due to the surface tension and viscosity of fluid **112** and the configuration of each opening **120**, the fluid will not pass out of the container thorough the opening unless the disk **100** is spinning at an angular velocity substantially greater than the normal playback velocity.

The fluidic structure may further comprise a channel **122** through which fluid **112** must pass before it reaches and corrupts the encoded-data portion **104** of disk **100**. The channel may be provided between disk layers and be generally closed along its length and open at both ends. Any number of channels may be provided to allow for fluid communication between each opening and the encoded area **104**. The channel may have any suitable cross-section, interior surface properties and length so as to slow droplets or streams of fluid passing through the opening and prevent fluid from reaching the encoded data until the disk **100** has been spun for a defined integral of angular velocity and time. For example, the channel may be designed so that fluid exiting the nozzles **120** does not reach the data area **104** until the disk has been spun for a period of time greater than, for example, one second, ten seconds, one minute, ten minutes, one hour, ten hours, or one-hundred hours at a normal playback velocity, and for correspondingly less time at greater velocities. Channel **122** may be provided in a linear, serpentine, labyrinth, coil, or any other desired course. It should be apparent that purely velocity-sensitive triggering devices and time-velocity sensitive devices may be combined in a single device.

In an embodiment, channel **122** and a fluid-containing portion of data area **104** may be configured so that fluid can flow back through the channel and into container **101** after it has been released. For example, the disk may include a funnel-shaped transition channel connecting a distal end of channel **122** to the data area **104**. Fluid released into the data area may then be funneled back into the channel by setting the disk on edge, so that gravity acts to pull released fluid back into the channel and container. This may permit functioning of the disk to be restored after a release event. In this embodiment, nozzle **120** may permit bidirectional flow of fluid, i.e., in or out of container **101**. In the alternative, nozzle **120** may be omitted.

FIG. **7** provides an illustration, in the form of a block diagram, of an additional disk or method for causing the rupture of a fluid container or other activation of a data-corrupting system. Specifically, a circuit-activated penetrating member system comprising a power source **303**, a force detecting sensor **302**, an actuator **301** and penetrating member **300** may be attached to the membrane **110** of a container **101**. These elements may be incorporated into a very small elec-

tronic device and secured to the disk, for example, by an adhesive label or by molding into the disk hub. The penetrating member **300** may be positioned adjacent to the membrane **110** so as to rupture the membrane when activated. The force detecting sensor **302** may measure any centrifugal force applied to the system as a result of the spinning of the disk, to which the system, through the container, is attached. The sensor **302** may also be configured to measure the sustained duration of any such centrifugal force, frequency or amplitude of vibration, or any other force or motion that may be caused by rotation of the disk at playback speed or higher, which are referred to generally herein as a "kinetic trigger." When the sensor **302** detects a kinetic trigger of sufficient duration, it may signal the actuator **301** which activates the penetrating member **300** which ruptures the membrane.

As used herein, a "kinetic trigger" means the occurrence of a defined condition caused by motion of the disk. For example, if a disk is spun at a rotational speed exceeding a defined threshold, physical conditions such as, for example, force, frequency or amplitude of vibration, strain, acceleration, temperature or frequency of optical pulse impinging in an area of a disk may be sensed and measured. Occurrence of a defined condition may serve as a trigger for activating any suitable data-obscuring device on the disk, such as described herein.

In other exemplary embodiments, an electro-optical material may be used to obscure some or all of the data encoded on a disk when a kinetic trigger is detected by a sensor on or in the disk. FIG. **8** is a schematic diagram showing an enlarged cross-section (not to scale) of an exemplary optical disk **800** with an electro-optical layer **802** also functioning as a data layer with encoded binary data **804** as pits formed in a substrate material of layer **802**. A first surface of layer **802**, in which the data **804** is encoded, may be coated with a reflective layer **806**, such as a metal layer. An adhesive layer **808** may be used to join the electro-optical layer **802** to a substrate or structural layer **810**. Focused laser light for reading encoded data may impinge on a reading surface **812** of the disk **800** and is reflected by metal layer **806**. Hence, the reading surface **812** and any layers intervening between the reading surface and the reflective layer **806**, such as electro-optical layer **802**, should be configured to transmit sufficient laser light to permit reading of encoded data, during normal operation. For example, electro-optical layer **802** may be more than 98% transparent, meaning blocking no more than 2% of transmitted or reflected light, unless activated.

Electro-optical layer **804** may be configured such that, when provided with an electrical signal, transparency of the layer decreases to a point where the encoded data is no longer readable by a typical optical media player. For example, transparency may decrease by 50% or more. Such a material may be referred to as "normally transmissive," because it transmits laser light unless exposed to an electrical signal causing it to become non-transmissive. In the alternative, the electro-optical material may be configured to be normally non-transmissive, meaning that will not transmit laser light until an electrical signal is applied.

The layer **804** may be made, for example, by dispersing an electrochromic material in a carrier substrate, by coating a surface of the electro-chromic layer with an electrochromic material, or by adhering an electrochromic laminate to a surface of the disk. Various suitable electrochromic materials are known in the art, and any suitable material may be used. For example, a suitable electrochromic material may comprise a cyanobiphenyl liquid crystal material in conjunction with polarizing filters, such as used in LCD displays. For further examples, the electrochromic material may comprise

a tungsten oxide material, an iridium oxide material, a methylene blue material, a bipyridium salt (viologen) material, or any suitable combination of these or other materials.

Disk **800** may further comprise opposing electrodes, with the electro-optical material interposed between the electrodes. For example, a metallic reflecting layer **806** may also serve as a conductive electrode. A second transparent electrode **814** may be disposed over the electro-optical layer **802**. A transparent electrode may be formed by depositing a transparent conductive oxide or nanotube dispersion over a suitable substrate. Transparent conductive coatings may comprise, for example, carbon nanotubes or nanoparticles, and/or gold, silver, tin-doped indium oxide (ITO), or other suitable material. Each electrode may be connected to a controller **816** configured to provide an electrical signal via a circuit **822**. The circuit **822** may be powered by a power source **818** and may include a sensor **820** operatively associated with the controller.

The power source **818** may comprise any suitable compact battery, fuel cell, generator or other power source small enough to be incorporated into disk **800** without interfering with normal operation of the disk, while being capable of activating the electro-optical material. To preserve power, controller **816** may include circuitry that activates the electro-optical layer **802** only when the disk is rotated, or only when a kinetic trigger is detected. At other times, the electro-optical material may remain inactivated and transparent. Suitable candidates for power source **818** may include, for example, a flexible thin layer open electrochemical cell as disclosed in Patent No. RE39,676; a thin film battery such as disclosed in U.S. Pat. Nos. 5,338,625 or 5,558,957; or a vibration-powered micro-electric generator, such as a piezoelectric generator or device as disclosed in U.S. Pat. No. 7,142,075. A device of the latter type may also serve as a vibration sensor, and thus, for applications where vibration provides a useful kinetic trigger, may also perform the functions of sensor **820** and/or of controller **816**.

Controller **816** may comprise a microprocessor, microcontroller or other control device coupled to control timing of an electrical signal provided to the electrodes **806**, **814**. Controller **816** may be coupled to receive signals from sensor **820** and may be configured to process the signals to determine whether a kinetic trigger has occurred. Upon occurrence of a kinetic trigger, the controller provides an electrical signal to the electrodes. For example, the controller may apply a voltage across the electrodes, and maintain the signal for a defined interval or intervals of time, for so long as the presence of the kinetic trigger is sensed, or for as long as the power source **818** permits, to activate a normally transmissive electro-optical material, thereby rendering it temporarily non-transmissive. The controller may comprise a programmable logic controller and a memory holding a program for processing signals from sensor **820** to recognize a kinetic trigger, and for controlling electrical signals applied to electrodes **806**, **814**.

In other embodiments, the controller may be configured to apply a voltage or other electrical signal via electrodes to a normally non-transmissive electro-optical layer. Upon occurrence of a kinetic trigger, the controller may remove the applied voltage or other electrical signal, causing the electro-optical material to assume its normal non-transmissive state.

Sensor **820** may comprise an accelerometer, strain gauge, photocell, thermistor, microphone, antenna or any other sensor or combination of sensors responsive to motion of the optical disk. In some embodiments, the sensor **820** may comprise a strain gauge disposed to sense changes in radial strain related to rotational movement and centripetal force. In other

embodiments, a similar function may be performed by an accelerometer directly sensing centripetal force or vibration. A photocell may detect fluctuations in light exposure that may be correlated to disk rotational speed. A filter may be incorporated into circuit **822** between the sensor and controller to filter extraneous signals. Circuit **822** may be formed as an integrated device.

Circuit **822** may be incorporated in a laminated assembly that is applied to the optical disk using a temporary or permanent adhesive. If applied using a temporary adhesive, the electro-optical layer may be configured to be normally non-transmissive, so that if the circuit is removed, the electro-optical layer will become non-transmissive.

FIG. 9 shows a partial plan view of an exemplary disk **900** with an electro-optical layer. An encoded area **902** of the disk comprises optically encoded data. Electro-optical layer may be provided over all of the encoded area, or over a portion **904** of the encoded area, as shown. A control circuit **922** such as described with reference to circuit **822** above may be provided in a device mounted inside an inner periphery **906** of disk **900**. In the alternative, the control circuit or some portion thereof may be placed outside an outer periphery **908** of the disk. A power source **918** may be configured to fit in an annular region between the inner periphery **906** of the encoded area and the hub mounting hole **912**. These components may be assembled during manufacture of the disk **900** and incorporated in it. In the alternative, the electrical and electro-optical components may be manufactured as a separate assembly that is applied to a finished disk.

In general, it may be desirable to provide the electro-optical layer and functionally related components in a laminated assembly configured to operate as an optical shutter for optical media. A configuration of electrical and electro-optical components as depicted in FIG. 9 may therefore be manufactured as a separate assembly and laminated to an optical disk after its manufacture. FIG. 10 is a schematic diagram showing an enlarged cross-section (not to scale) of an exemplary disk **100** with an electro-optical layer **1004**, in a configuration suitable for manufacture as a separate laminated assembly **1030**. Data layer **1002**, reflective surface **1006**, adhesive layer **1008**, and lower layer **1010** may comprise conventional components and materials used in optical data disks. Laminated assembly **1030** may be applied to transparent surface of disk **1000** over the encoded substrate **1002**. Assembly **1030** may incorporate a control circuit **1022** in a portion of the assembly that is not applied over the encoded substrate. The control circuit may comprise a controller **1016**, sensor **1020** and power source **1018** as described above in connection with FIG. 8.

Assembly **1030** may comprise three layers: a first transparent electrode **1016** disposed against encoded substrate **1002**; a second transparent electrode **1014** parallel to and disposed over the first electrode, and having an outer reading surface **1012**; and an electro-optical layer **1004** interposed between the first and second electrodes. The depicted configuration is merely exemplary, and any suitable assembly providing the function of an optical shutter may be used, for example as used in LCD displays and optical devices. The laminated assembly may be constructed using flexible polymer films laminated together with suitable adhesives or thermally bonded, and may comprise electrochromic and transparent conductive materials as previously described.

According to the foregoing, therefore, an optical disk may be configured with one of the foregoing containers, layers, membranes, or devices configured to render encoded data on the disk unreadable if the disk is spun at an angular velocity substantially greater than a playback angular velocity used

11

for normal reading of the encoded data by an end user device, for example, by a CD player, an DVD player, a HD-DVD player, or a Blu-Ray™ player, to produce an audio-visual output. In an embodiment, the container, layer, membrane or device is configured to render the disk unreadable if the disk angular velocity exceeds the playback angular velocity by at least 50%. In other embodiments, the container, layer, membrane or device may be configured to render the disk unreadable if the disk angular velocity exceeds the playback angular velocity by one of at least 100%, 500%, 1000%, 1500%, 2000%, or 2500%. In the alternative, or in addition, the container, layer, membrane or device may be configured to render the disk unreadable if the disk angular velocity exceeds the playback angular velocity by at least any of the foregoing thresholds or by any amount for a period of time, or by an integral of angular velocity and time. In the alternative, the container, layer, membrane or device may be configured to render the disk unreadable if the disk angular velocity does not exceed the playback angular velocity, but if the integral of angular velocity and time exceeds a defined threshold, to provide a disk that that cannot be spun and remain readable for more than a limited amount of playing time.

Having thus described an embodiment of an optically-readable disk designed to inhibit the copying of the content recorded on it by rendering the disk unreadable at a speed substantially higher than the disk's standard playback speed, it should be apparent to those skilled in the art that certain advantages of the within system have been achieved. It should also be appreciated that various modifications, adaptations, and alternative embodiments thereof may be made within the scope and spirit of the present invention. The invention is defined by the following claims.

What is claimed is:

1. An optically-readable disk comprising:
a reflective surface having data encoded therein;
a reading surface disposed over the reflective surface, the reading surface configured to transmit laser light for reading the data encoded in the reflective surface;
an electro-optical material interposed between the reading surface and the reflective surface, the electro-optical material configured to have an optical property that changes in response to an electrical signal;
a controller coupled to the electro-optical material and configured to provide the electrical signal in response to sensor input; and
a sensor coupled to the controller and configured to provide the sensor input to the controller in response to rotational motion of the disk.
2. The optically-readable disk of claim 1, further comprising a transparent conducting layer disposed over the electro-optical material and coupled to the controller.
3. The optically-readable disk of claim 2, wherein the transparent conducting layer comprises an indium tin oxide material.
4. The optically-readable disk of claim 2, wherein the transparent conducting layer comprises conductive nanotubes dispersed in a polymer matrix.

12

5. The optically-readable disk of claim 1, further comprising an electrode disposed adjacent to the electro-optical material and coupled to the controller.

6. The optically-readable disk of claim 1, further comprising an electrical battery coupled to the controller.

7. The optically-readable disk of claim 1, wherein the sensor comprises an accelerometer.

8. The optically-readable disk of claim 1, wherein the sensor comprises a photocell.

9. The optically-readable disk of claim 1, wherein the electro-optical material comprises a liquid crystal material.

10. The optically-readable disk of claim 1, wherein the electro-optical material comprises an electrochromic material.

11. The optically-readable disk of claim 1, wherein the electro-optical material comprises an electrochromic film adhered to a surface of the disk over the reflective surface.

12. The optically-readable disk of claim 11, further comprising an electrode disposed over at least one surface of the electrochromic film.

13. The optically-readable disk of claim 1, wherein the controller and sensor are attached to the electrochromic film.

14. The optically-readable disk of claim 1, wherein the electro-optical material covers less than an entirety of the reflective surface.

15. The optically-readable disk of claim 1 wherein the optical property of the electro-optical material is selected from the group consisting of: transparency, reflectivity, or color.

16. A laminated assembly configured to operate as an optical shutter for an optical media containing encoded data;
a first transparent conducting layer configured for bonding to an outer surface of the optical media;
a second transparent conduction layer disposed parallel to the first transparent conducting layer;
an electro-optical layer interposed between the first transparent conducting layer and the second transparent conducting layer, the electro-optical layer having at least one optical property that changes in response to an electrical signal;
a controller coupled to the electro-optical material and configured to provide the electrical signal in response to sensor input; and
a sensor coupled to the controller and configured to provide the sensor input to the controller in response to rotational motion of the laminated assembly.

17. The laminated assembly of claim 1, further comprising an electrical battery coupled to the controller.

18. The laminated assembly of claim 1, wherein the sensor comprises an accelerometer.

19. The laminated assembly of claim 1, wherein the sensor comprises a strain gauge.

20. The laminated assembly of claim 1, wherein the sensor comprises a photo cell.

* * * * *